

**SPECIAL BOILING POINT 100/140****Code : 16429****Responsible for distribution:**

BRENNTAG N.V.  
Nijverheidslaan 38 - BE-8540 DEERLIJK  
TEL: +32(0)56/77.69.44 - FAX: +32(0)56/77.57.11  
E-MAIL : info@brenntag.be - Website: www.brenntag.be

BRENNTAG Nederland B.V.  
Donker Duyvisweg 44 - NL-3316 BM DORDRECHT  
TEL: +31(0)78/65.44.944 - FAX: +31(0)78/65.44.919  
E-MAIL : info@brenntag.nl - Website: www.brenntag.nl

**In case of emergency:**

Belgium:  
Antipoison Center - Brussels :  
TEL: 070/245.245

The Netherlands:  
National Poisoning Information Center - Bilthoven :  
TEL: 030/274.88.88

**1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Chemical description : Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics .  
Type of product : Dearomatized hydrocarbons .  
Reach registration number : 01-2119473851-33

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Identified use(s) : See table on the front page of the annex.  
Use(s) advised against : This product is not recommended for any industrial, professional or consumer use other than identified in table on the front page of the annex.

**1.3. Details of the supplier of the safety data sheet**

Company identification : See heading of Material Safety Data Sheet.

**1.4. Emergency telephone number**

Emergency phone number : See heading of Material Safety Data Sheet.

**2. Hazards identification****2.1. Classification of the substance or mixture****Classification according to Directive 67/548/EEC or 1999/45/EC**

Highly flammable (F; R11)  
Dangerous for the environment (N; R51/53)  
Harmful (Xn; R65)  
Other (R66-67)

**Classification according to Regulation (EC) No 1272/2008**

Flammable liquids - Category 2 - Danger (Flam. Liq. 2; H225)  
Aspiration hazard - Category 1 - Danger (Asp. Tox. 1; H304)  
Specific Target Organ Toxicity - Single exposure - Narcotic effects - Category 3 - Warning (STOT SE 3; H336)  
Hazardous to the aquatic environment - Chronic hazard - Category 2 (Aquatic Chronic 2; H411)  
Specific Target Organ Toxicity - Repeated exposure - Skin dryness or cracking (STOT RE; EUH066)

**2.2. Label elements****Label in accordance with Regulation (EC) No 1272/2008**

- Dangerous ingredient(s) : Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
- Hazard pictogram(s)



- Signal word : Danger

**SPECIAL BOILING POINT 100/140**

**Code : 16429**

**2. Hazards identification (continued)**

- Hazard statements : H225 - Highly flammable liquid and vapour. H304 - May be fatal if swallowed and enters airways. H336 - May cause drowsiness or dizziness. H411 - Toxic to aquatic life with long lasting effects. EUH066 - Repeated exposure may cause skin dryness or cracking.
- Precautionary statements
  - Prevention : P210 - Keep away from heat, sparks, open flames or hot surfaces. – No smoking. P261 - Avoid breathing dust, fume, gas, mist, vapours, spray. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, face protection.
  - Response : P301+P310+P331 - IF SWALLOWED : Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
  - Disposal considerations : P501 - Dispose of contents and/or container in accordance with local, regional, national and/or international regulation.

**2.3. Other hazards**

- Physical/chemical hazards : May generate static electric discharges.
- Hazards for the health : Exposure to high doses may cause depression of the central nervous system.
- Hazards for the environment : No additional hazard. This product is no substance or contains no PBT or vPvB (in accordance with Annex XIII).
- Hazards for the safety : At or above flash point, available vapours may burn in open or explode if confined when mixed with air and exposed to ignition source.

**3. Composition/information on ingredients**

**3.1. Substances**

Name component(s)	Weight %	CAS nr	EINECS nr	Index nr	Reach nr	CLASSIFICATION
Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics	100 %	----	920-750-0	----	01-2119473851-33	F; R11 Xn; R65 R66 R67 N; R51-53 ----- Flam. Liq. 2; H225 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 2; H411 STOT RE; EUH066

The full text of the R-phrases and (EU)H-statements is in section 16.

Note: Any entry in the EC# (or EINECS#) column that begins with the number "9" is a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

**4. First aid measures**

**4.1. Description of first aid measures**

- General : In case of doubt or persistent symptoms, call a physician.  
Never give anything by mouth to an unconscious person.
- First Aid Measures
  - Inhalation : Remove victim into fresh air.  
Allow the affected person to rest.  
If not breathing, give artificial respiration.  
If symptoms, consult doctor.

**SPECIAL BOILING POINT 100/140****Code : 16429****4. First aid measures (continued)**

- Skin Contact : Remove contaminated clothing.  
Rinse skin immediately with mild soap and plenty of water. (shower if necessary).  
Consult doctor if irritation develops.
- Eye Contact : Rinse immediately thoroughly and long (at least 15 min.) with plenty of water.  
Remove contact lenses.  
Consult eye doctor if irritation of eyes develops.
- Ingestion : DO NOT INDUCE VOMITING.  
Rinse mouth with water.  
Seek medical attention IMMEDIATELY or take to hospital.

**4.2. Most important symptoms and effects, both acute and delayed**

See section 11.

**4.3. Indication of any immediate medical attention and special treatment needed**

For specialist advice doctors should contact the NVCI or the Belgian Poison center.

**5. Firefighting measures****5.1. Extinguishing media**

Extinguishing Media

- Suitable : Extinguishing powder , Foam , Carbon dioxide (CO2) . Water spray .
- Unsuitable : Heavy water stream .

**5.2. Special hazards arising from the substance or mixture**

Special Exposure Hazards : Fire may liberate carbon oxides (CO) and smoke.

**5.3. Advice for firefighters**

- Special Protective Equipment for Firefighters : Use self-contained breathing apparatus and wear protective clothes when in close proximity to fire.
- Special Procedures : Apply water spray or fog to cool nearby equipment. Avoid fire-fighting water to enter environment.

**6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Personal Precautions : Eliminate every possible source of ignition (open fire, sparks, smoking, ...).  
Evacuate all personnel immediately and ventilate area.  
Avoid breathing vapour and contact with skin, eyes and clothing. Wear recommended personal protective equipment. (See section 8)

**6.2. Environmental precautions**

Environmental Precautions : Shut off leaks if without risks.  
Dike in the spilled product as much as possible with inert material.  
Prevent entry of product in public water, sewers or soil.  
Notify authorities if product enters sewers or public waters.

**6.3. Methods and material for containment and cleaning up**

Methods for Cleaning Up : Collect the spillage in closable, suitable disposal containers.  
Clean up any spills as soon as possible, using an inert absorbent material.  
Residue is to be washed down with plenty of water.

**6.4. Reference to other sections**

For personal protection, see section 8.  
For the removal of the waste product, see section 13.

**SPECIAL BOILING POINT 100/140**

**Code : 16429**

**7. Handling and storage**

**7.1. Precautions for safe handling**

Handling : Avoid breathing vapour and contact with skin, eyes and clothing. Wear recommended personal protective equipment. (See section 8)  
Wash hands before and after working with the product.  
When using, do not eat, drink or smoke.  
Emergency eye wash fountains and showers should be available in the immediate vicinity of any potential exposure.

**7.2. Conditions for safe storage, including any incompatibilities**

Storage : Keep only in the original, safely locked container in a well ventilated, cool and dark place.  
All dangerous products should be placed on a drip tray or should be barreled.  
Store away from all heat sources, including direct sunlight.  
Keep away from : Strong oxidizing agents .

Protection against Fire and Explosion : Remove all sources of ignition (open fire, sparks, smoking, ...).  
Vapour is heavier than air and spreads along the ground with risk of ignition on distance.  
Do not use compressed air to either agitate or transfer contents of storage containers (tanks) / shipping drums containing this material.  
Take measures against electrostatic discharges.  
Use explosionproof equipment.  
Sufficiently earthen.

Packaging Material : Carbon steel , Stainless steel , Polyethylene , Polypropylene , Teflon , Polyester .

Insuitable Packaging Material : Natural rubber , Butyl rubber , EPDM, Polystyrene .

**7.3. Specific end use(s)**

For identified uses, see subsection 1.2 and/or exposure scenarios.

**8. Exposure controls/personal protection**

**8.1. Control parameters**

Occupational Exposure Limits : Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : Recommended limit (RCP-TWA) (Producer) : 260 ppm (1200 mg/m<sup>3</sup>) ( Total hydrocarbons )

Biological limit values : They will be included when available.

DNELs : • Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : Worker, long-term - local effects, inhalation : 2035 mg/m<sup>3</sup>  
• Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : Worker, long-term - systemic effects, inhalation : 2035 mg/m<sup>3</sup>  
• Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : Worker, long-term - systemic effects, dermal : 773 mg/kg bw/ day  
• Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : Consumer, long-term - local effects, oral : 699 mg/kg  
• Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : Consumer, long-term - systemic effects, inhalation : 608 mg/m<sup>3</sup>  
• Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : Consumer, long-term - systemic effects, dermal : 699 mg/kg bw/ day  
• Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : Consumer, long-term - systemic effects, oral : 699 mg/kg

PNECs : Not applicable.

**8.2. Exposure controls**

Engineering Measures : Ventilation , Local exhaust .

Personal Protection Equipment

**SPECIAL BOILING POINT 100/140**

**Code : 16429**

**8. Exposure controls/personal protection (continued)**

- Respiratory protection : CE-approved mask for organic vapours and solvents (type A, brown).
- Skin protection : Suitable protective clothing . ( Anti-static )
- Hand protection : Suitable material for safety gloves (EN 374):  
Nitril rubber : penetration time > 480' - thickness 0,40 mm
- Eye/Face protection : Closed safety glasses or face shield.
- Environmental exposure controls : See sections 6, 7, 12 en 13.

**9. Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

- Physical State (20°C) : Liquid .
- Form/Colour : Clear , Colourless .
- Odour : Weak petroleum odour odour.
- Odour threshold : No data available.
- pH value : Not applicable.
- Melting/Freezing point : < -20 °C
- Boiling Point/Range (1013 hPa) : 90 - 165 °C
- Flash point : 1 °C
- Fire hazard : P1
- Evaporation rate : 1,9 ( n-Butyl acetate = 1)  
6 ( Diethyl ether =1)
- Explosion limits in air : 0,6 - 7,0 vol.%
- Vapour pressure : 1,5 kPa (0°C)  
3,5 kPa (20°C)  
12 kPa (50°C)
- Relative vapour density (air=1) : > 1 (101 kPa)
- Density : 0,710 - 0,780 kg/l (15°C)
- Solubility in water : Insoluble .
- Soluble in : Aliphatic hydrocarbons , Aromatic hydrocarbons .
- Log P Octanol/Water (20°C) : Not established.
- Auto-ignition temperature : > 200 °C
- Minimum ignition energy : No data available.
- Decomposition temperature : No data available.
- Viscosity (25°C) : 0,76 mm<sup>2</sup>/s ( Kinematic )
- Explosive properties : No chemical groups associated with explosive properties .
- Oxidizing properties : No chemical groups associated with oxidizing properties .

**9.2. Other information**

- Surface tension (20°C) : 21,9 mN/m
- Specific leading : 0,9 pS/m
- Thermal expansion coefficient : 0,00114 v/v °C
- % Volatiles (by weight) : 85

**10. Stability and reactivity**

**10.1. Reactivity**

**SPECIAL BOILING POINT 100/140**

**Code : 16429**

**10. Stability and reactivity (continued)**

Reactivity : Reacts with : Strong oxidizing agents .

**10.2. Chemical stability**

Stability : Stable at normal circumstances .

**10.3. Possibility of hazardous reactions**

Hazardous reactions : Not known .

**10.4. Conditions to avoid**

Conditions to avoid : High temperatures .

**10.5. Incompatible materials**

Materials to avoid : Strong oxidizing agents .

**10.6. Hazardous decomposition products**

Hazardous Decomposition Products : Does not decompose at room temperature .  
Fire may liberate carbon oxides (CO) and smoke.

**11. Toxicological information**

**11.1. Information on toxicological effects**

Acute toxicity

- Inhalation : Minimal toxicity.  
Exposure to high concentrations may cause lowering of consciousness.  
Symptoms include: Dizziness , Headache , Nausea , Unconsciousness .  
• Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : LC50 (Rat, inhalation, 4 h) : > 23,3 mg/l
- Skin contact : Irritating to skin.  
Symptoms include: Redness , Pain .  
• Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : LD50 (Rabbit, dermal) : > 2800 mg/kg
- Eye contact : Slight, short-term discomfort of the eyes .
- Ingestion : After swallowing, some drops of liquid can enter the lungs (aspiration), which may cause pneumonia.  
• Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : LD50 (Rat, oral) : > 5000 mg/kg

Skin corrosion/irritation : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation : Not irritant .

Aspiration hazard : May be fatal if swallowed and enters airways.

Respiratory or skin sensitisation : Not sensitive .

Carcinogenicity : Not listed as carcinogenic .

Mutagenicity : Not listed as mutagenic .

Reproductive toxicity : Not listed for reproductive toxicity .

Specific target organ toxicity - single exposure : To human : Vapours may cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure : To human : Listed not for organ toxicity .  
For animals : Effects on kidneys.

**12. Ecological information**

**12.1. Toxicity**

**SPECIAL BOILING POINT 100/140**

**Code : 16429**

**12. Ecological information (continued)**

Ecotoxicity : • Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : EC50 (Daphnia magna, 48 h) : 4,6 mg/l  
 • Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : EC50 (Algae, 72 h) : 10 mg/l (Pseudokirchneriella subcapitata)  
 • Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : LC50 (Fish, 96 h) : 3-10 mg/l (Oncorhynchus mykiss)

**12.2. Persistence and degradability**

Persistence and degradability : • Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : Persistence and degradability : Expected to be easily biodegradable.

**12.3. Bioaccumulative potential**

Bioaccumulation : • Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : Bioaccumulation : No data available.

**12.4. Mobility in soil**

Mobility : • Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : Mobility : Floats on the water .

**12.5. Results of PBT and vPvB assessment**

Evaluation : • Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics : PBT/vPvB : No

**12.6. Other adverse effects**

WGK class (DE) : 2 ( Water pollutant ).

Photochemical ozone creation potential : No data available.

Ozone depletion potential : No data available.

Endocrine disrupting potential : No data available.

Global warming potential : No data available.

**13. Disposal considerations**

**13.1. Waste treatment methods**

Waste from residues/Unused products : The product has to be destroyed according to national or local legislation, by a company specialised in handling hazardous waste products.

European list of waste products : XXXXXX - European waste product code. This code is assigned on the basis of the most current applications and can not be representative for pollutions which are arisen at the effective use of the product. The producer of the waste has to evaluate its process himself and has to grant the appropriate waste coding. See Decision 2001/118/EC.

Removal contaminated packaging : Packing is to be used exclusively for the packing of this product. After use, empty and close the packing very carefully. In case of returned packing, the empty packing can be offered back to the supplier.

**14. Transport information**

**14.1. UN number**

UN Number : 3295

**14.2. UN proper shipping name**

ADR Name : UN 3295 Hydrocarbons, liquid, n.o.s., (contains Hydrocarbons C7-C9, n-alkanes, isoalkanes, cyclics), 3, II, (D/E), SP 640D

ADN Name : UN 3295 Hydrocarbons, liquid, n.o.s. , ( Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics ), 3, II

**SPECIAL BOILING POINT 100/140**

**Code : 16429**

**14. Transport information (continued)**

IMDG Name : UN 3295 Hydrocarbons, liquid, n.o.s. , (contains Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics), 3, II, (1°C), MARINE POLLUTANT

**14.3. Transport hazard classe(s)**

Class : 3

**14.4. Packing group**

Packaging Group : II

**14.5. Environmental hazards**

Environmentally hazard : Yes

Marine pollutant : Yes

**14.6. Special precautions for user**

Danger number : 33

Hazard Label(s) : 3

EmS-N° : F-E , S-D

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Type ship : 2

Pollution category : X

**15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Inventories : Australian inventory (AICS): Listed in inventory.  
 Canadian inventory (DSL): Listed in inventory.  
 Chinese inventory (IECS): Listed in inventory.  
 European inventory (EINECS): Listed in inventory.  
 Korean inventory (KECI): Listed in inventory.  
 Philippine inventory (PICCS): Listed in inventory.  
 Inventory of the United States (TSCA): Listed in inventory.

Relevant EU Rule(s) : Directive 96/82/EC of the Council of 9 December 1996 on the control of major-accident hazards involving dangerous substances  
 Directive 98/24/EC of the Council of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work  
 Directive 1999/13/EC of the Council of 11 March 1999 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain activities and installations  
 Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC  
 Decision 2001/118/EC of the Commission of 16 January 2001 amending Decision 2000/532/EC as regards the list of wastes  
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006  
 Regulation (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (Reach)

**15.2. Chemical Safety Assessment**



**SPECIAL BOILING POINT 100/140****Code : 16429****15. Regulatory information (continued)**

A chemical safety assessment has been carried out for the substance(s) that make up this material or for the material itself.

**16. Other information**

This safety data sheet has been drawn up in accordance with Regulation (EU) No 453/2010.  
This safety data sheet is exclusively made for industrial/professional use.

- Sources of used key data : The information contained herein is based on the present state of our knowledge ( Producer(s) , ...).  
See also on the webaddress:  
<http://apps.echa.europa.eu/registered/registered-sub.aspx#search>
- R-phrases(s) : R11 - Highly flammable.  
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65 - Harmful : may cause lung damage if swallowed.  
R66 - Repeated exposure may cause skin dryness or cracking.  
R67 - Vapours may cause drowsiness and dizziness.
- (EU)H-statement(s) : H225 - Highly flammable liquid and vapour.  
H304 - May be fatal if swallowed and enters airways.  
H336 - May cause drowsiness or dizziness.  
H411 - Toxic to aquatic life with long lasting effects.  
EUH066 - Repeated exposure may cause skin dryness or cracking.
- List of abbreviations and acronyms : ADN (Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation interieur) : European agreement concerning the international carriage of dangerous goods by inland waterways  
ADR (Accord européen relatif au transport international des marchandises Dangereuses par Route) : European agreement concerning the international carriage of dangerous goods by road  
CO : Carbon monoxide  
DNEL (Derived No Effect Level) : an estimated safe exposure level  
EmS (Emergency Schedule) : the first code refers to the relevant fire schedule and the second code refers to the relevant spillage schedule  
IMDG (International Maritime Dangerous Goods code)  
NVCI : National Poisoning Information Center  
PBT : persistent, bioaccumulative and toxic  
PNEC (Predicted No Effect Concentration) : concentration below which exposure to a substance is not expected to cause adverse effects  
REACH : Registration, Evaluation, Authorisation and restriction of Chemicals  
vPvB : very persistent and very bioaccumulative  
WGK (Wassergefährdungsklasse) : a German classification of substances that indicate the environmental hazard for surface water

This information is to our knowledge correct and complete on the date of issue of this safety data sheet. The information only concerns the product and does not give any guarantee for the quality and the completeness of the properties of the product, or in case of mixing or using in any other process. It remains the responsibility of the user to assure himself that the information is suitable and complete concerning the special use he makes of the product.  
BRENNTAG denies all responsibility for loss or damage resulting from the use of these data.

End of document

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

No.	Short title	Main User Group (SU)	Sector of Use (SU)	Product Category (PC)	Process Category (PROC)	Environmental Release Category (ERC)	Article Category (AC)	Specified
1	Manufacture of substance	3	8, 9	NA	1, 2, 3, 4, 8a, 8b, 15	1, 4	NA	ES5247
2	Distribution of substance	3	8, 9	NA	1, 2, 3, 4, 8a, 8b, 9, 15	1, 2, 3, 4, 5, 6a, 6b, 6c, 6d, 7	NA	ES5250
3	Formulation & (re)packing of substances and mixtures	3	10	NA	1, 2, 3, 4, 5, 8a, 8b, 9, 14, 15	2	NA	ES5252
4	Rubber production and processing	3	10, 11	NA	1, 2, 3, 4, 5, 6, 7, 8a, 8b, 9, 13, 14, 15, 21	1, 4, 6d	NA	ES5270
5	Polymer processing	3	10	NA	1, 2, 3, 4, 5, 6, 8a, 8b, 9, 13, 14, 21	4	NA	ES5273
6	Uses in coatings	3	NA	NA	1, 2, 3, 4, 5, 7, 8a, 8b, 9, 10, 13, 14, 15	4	NA	ES5254
7	Uses in coatings	22	NA	NA	1, 2, 3, 4, 5, 8a, 8b, 10, 11, 13, 15, 19	8a, 8d	NA	ES5275
8	Uses in coatings	21	NA	1, 4, 8, 9a, 9b, 9c, 15, 18, 23, 24, 31, 34	NA	8a, 8d	NA	ES5295
9	Use in Cleaning Agents	3	NA	NA	1, 2, 3, 4, 7, 8a, 8b, 10, 13	4	NA	ES5256
10	Use in Cleaning Agents	22	NA	NA	1, 2, 3, 4, 8a, 8b, 10, 11, 13	8a, 8d	NA	ES5277
11	Use in Cleaning Agents	21	NA	3, 4, 8, 9a, 9b, 9c, 24, 35, 38	NA	8a, 8d	NA	ES5542
12	Use as binders and release agents	3	NA	NA	1, 2, 3, 4, 6, 7, 8b, 10, 13, 14	4	NA	ES5262
13	Use as binders and	22	NA	NA	1, 2, 3, 4,	8a, 8d	NA	ES5284

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	release agents				6, 8a, 8b, 10, 11, 14			
14	Use as a fuel	3	NA	NA	1, 2, 3, 8a, 8b, 16	7	NA	ES5264
15	Use as a fuel	22	NA	NA	1, 2, 3, 8a, 8b, 16	9a, 9b	NA	ES5286
16	Use as a fuel	21	NA	13	NA	9a, 9b	NA	ES5535
17	Use as lubricants	3	NA	NA	1, 2, 3, 4, 7, 8a, 8b, 9, 10, 13, 17, 18	4, 7	NA	ES5258
18	Use as lubricants	22	NA	NA	1, 2, 3, 4, 8a, 8b, 9, 10, 11, 13, 17, 18, 20	8a, 8d, 9a, 9b	NA	ES5279
19	Use as lubricants	21	NA	1, 24, 31	NA	8a, 8d, 9a, 9b	NA	ES5520
20	Use as Functional Fluids	3	NA	NA	1, 2, 3, 4, 8a, 8b, 9	7	NA	ES5266
21	Use as Functional Fluids	22	NA	NA	1, 2, 3, 8a, 9, 20	9a, 9b	NA	ES5288
22	Use as Functional Fluids	21	NA	16, 17	NA	9a, 9b	NA	ES5533
23	Use in laboratories	3	NA	NA	10, 15	2, 4	NA	ES5268
24	Use in laboratories	22	NA	NA	10, 15	8a	NA	ES5292
25	Use in metal working fluids / rolling oils	3	NA	NA	1, 2, 3, 4, 5, 7, 8a, 8b, 9, 10, 13, 17	4	NA	ES5260
26	Use in metal working fluids / rolling oils	22	NA	NA	1, 2, 3, 8a, 8b, 9, 10, 11, 13, 17	8a, 8d	NA	ES5282
27	Use in road and construction applications	22	NA	NA	8a, 8b, 10, 11, 13	8d, 8f	NA	ES5290
28	Other consumer uses	21	NA	28, 39	NA	8a, 8d	NA	ES7865

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 1: Manufacture of substance**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU8: Manufacture of bulk, large scale chemicals (including petroleum products) SU9: Manufacture of fine chemicals
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC15: Use as laboratory reagent
Environmental Release Categories	ERC1: Manufacture of substances ERC4: Industrial use of processing aids in processes and products, not becoming part of articles
Activity	Manufacture of the substance or use as a process chemical or extraction agent within closed or contained systems. Includes incidental exposures during recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container)

**2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC4**

Amount used	Maximum daily site tonnage (kg/day):	45000 kg/day
	Regional use tonnage (tons/year):	4500 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	1
	Annual site tonnage (tons/year):	4500 ton(s)/year
Frequency and duration of use	Continuous exposure	100 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	5,0 .10 <sup>-2</sup>
	Emission or Release Factor: Water	3,0 .10 <sup>-5</sup>

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Emission or Release Factor: Soil	1,0 .10-4
	initial release prior to RMM	
<p>Technical conditions and measures at process level (source) to prevent release          Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil          Organizational measures to prevent/limit release from the site</p>	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
	Sediment	Risk from environmental exposure is driven by freshwater sediment.
	Common practices vary across sites thus conservative process release estimates used.	
<p>Conditions and measures related to sewage treatment plant</p>	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	10.000 m3/d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
<p>Conditions and measures related to external treatment of waste for disposal</p>	Waste treatment	During manufacturing no waste of the substance is generated.
<p>Conditions and measures related to external recovery of waste</p>	Recovery Methods	During manufacturing no waste of the substance is generated.
<p><b>2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15</b></p>		
<p>Product characteristics</p>	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
<p>Frequency and duration of use</p>	Frequency of use	8 hours/day
<p>Other operational conditions affecting workers exposure</p>	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
<p>Technical conditions and measures to control dispersion</p>	General exposures (closed systems)	Handle substance within a closed system.(PROC1)
P5894	4/118	EN

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

from source towards the worker	General exposures (closed systems) Use in contained batch processes	Handle substance within a closed system.(PROC2)
	Storage	Store substance within a closed system.(PROC1, PROC2)

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	4300000 kg/day	---

ESVOC spERC 1.1v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 2: Distribution of substance**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU8: Manufacture of bulk, large scale chemicals (including petroleum products) SU9: Manufacture of fine chemicals
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC15: Use as laboratory reagent
Environmental Release Categories	ERC1: Manufacture of substances ERC2: Formulation of preparations ERC3: Formulation in materials ERC4: Industrial use of processing aids in processes and products, not becoming part of articles ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates) ERC6b: Industrial use of reactive processing aids ERC6c: Industrial use of monomers for manufacture of thermoplastics ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers ERC7: Industrial use of substances in closed systems

**2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7**

Amount used	Maximum daily site tonnage (kg/day):	42 kg/day
	Regional use tonnage (tons/year):	422 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,002
	Annual site tonnage (tons/year):	0,84 ton(s)/year
Frequency and duration of use	Continuous exposure	20 days/year
Environment factors not	Dilution Factor (River)	10

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

influenced by risk management	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	1,0 .10 <sup>-3</sup>
	Emission or Release Factor: Water	1,0 .10 <sup>-6</sup>
	Emission or Release Factor: Soil	1,0 .10 <sup>-5</sup>
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
	Water	Risk from environmental exposure is driven by freshwater.
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to sewage treatment plant	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
Conditions and measures related to external treatment of waste for disposal	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
<b>2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
P5894	7/118	EN



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Other operational conditions affecting workers exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1)
	General exposures (closed systems)	Handle substance within a closed system.(PROC2)
	General exposures (closed systems)	Handle substance within a closed system.(PROC3)
	Storage	Store substance within a closed system. Transfer via enclosed lines.(PROC1, PROC2)

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	620000 kg/day	---

ESVOC spERC 1.1b.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 3: Formulation & (re)packing of substances and mixtures**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 10: Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation</p> <p>PROC15: Use as laboratory reagent</p>
Environmental Release Categories	ERC2: Formulation of preparations

**2.1 Contributing scenario controlling environmental exposure for: ERC2**

Amount used	Maximum daily site tonnage (kg/day):	1200 kg/day
	Regional use tonnage (tons/year):	120 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	1
	Annual site tonnage (tons/year):	120 ton(s)/year
Frequency and duration of use	Continuous exposure	100 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	2,5 .10 <sup>-2</sup>
	Emission or Release Factor: Water	2,0 .10 <sup>-5</sup>
	Emission or Release	1,0 .10 <sup>-4</sup>

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Factor: Soil	
	initial release prior to RMM	
<p>Technical conditions and measures at process level (source) to prevent release          Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil          Organizational measures to prevent/limit release from the site</p>	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 0 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
	Sediment	Risk from environmental exposure is driven by freshwater sediment.
	Common practices vary across sites thus conservative process release estimates used.	
<p>Conditions and measures related to sewage treatment plant</p>	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m3/d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
<p>Conditions and measures related to external treatment of waste for disposal</p>	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
<p>Conditions and measures related to external recovery of waste</p>	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
<p><b>2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15</b></p>		
<p>Product characteristics</p>	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
<p>Frequency and duration of use</p>	Frequency of use	8 hours/day
<p>Other operational conditions affecting workers exposure</p>	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
<p>Technical conditions and measures to control dispersion</p>	General exposures	Handle substance within a closed system.(PROC1)
P5894	10/118	EN

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

from source towards the worker	(closed systems)	
	General exposures (closed systems)	Handle substance within a closed system.(PROC2)
	General exposures (closed systems)	Handle substance within a closed system.(PROC3)
	Storage	Store substance within a closed system.(PROC1, PROC2)

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	1300000 kg/day	---

ESVOC spERC 2.2.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 4: Rubber production and processing**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 10: Formulation [mixing] of preparations and/ or re-packaging (excluding alloys) SU11: Manufacture of rubber products
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) PROC6: Calendering operations PROC7: Industrial spraying PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC13: Treatment of articles by dipping and pouring PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation PROC15: Use as laboratory reagent PROC21: Low energy manipulation of substances bound in materials and/or articles
Environmental Release Categories	ERC1: Manufacture of substances ERC4: Industrial use of processing aids in processes and products, not becoming part of articles ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

**2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC4, ERC6d**

Amount used	Maximum daily site tonnage (kg/day):	250 kg/day
	Regional use tonnage (tons/year):	5 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	1
	Annual site tonnage (tons/year):	5 ton(s)/year
Frequency and duration of use	Continuous exposure	20 days/year

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	1,0 .10 <sup>-2</sup>
	Emission or Release Factor: Water	3,0 .10 <sup>-5</sup>
	Emission or Release Factor: Soil	1,0 .10 <sup>-4</sup>
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 0 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
	Sediment	Risk from environmental exposure is driven by freshwater sediment.
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to sewage treatment plant	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
Conditions and measures related to external treatment of waste for disposal	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC21**

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Other operational conditions affecting workers exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk weighing	Handle substance within a closed system.(PROC1)
	Bulk weighing	Handle substance within a closed system.(PROC2)
	Storage	Store substance within a closed system.(PROC1, PROC2)

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	850000 kg/day	---

ESVOC spERC 4.19a.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 5: Polymer processing**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 10: Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC6: Calendering operations</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation</p> <p>PROC21: Low energy manipulation of substances bound in materials and/or articles</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

**2.1 Contributing scenario controlling environmental exposure for: ERC4**

Amount used	Maximum daily site tonnage (kg/day):	1600 kg/day
	Regional use tonnage (tons/year):	32 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	1
	Annual site tonnage (tons/year):	32 ton(s)/year
Frequency and duration of use	Continuous exposure	20 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	0,5



**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Emission or Release Factor: Water	1,0 · 10 <sup>-5</sup>
	Emission or Release Factor: Soil	0
	initial release prior to RMM	
<p>Technical conditions and measures at process level (source) to prevent release            Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil            Organizational measures to prevent/limit release from the site</p>	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 80 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
	Water	Risk from environmental exposure is driven by freshwater.
	Common practices vary across sites thus conservative process release estimates used.	
<p>Conditions and measures related to sewage treatment plant</p>	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
<p>Conditions and measures related to external treatment of waste for disposal</p>	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
<p>Conditions and measures related to external recovery of waste</p>	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
<p><b>2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC21</b></p>		
<p>Product characteristics</p>	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
<p>Frequency and duration of use</p>	Frequency of use	8 hours/day
P5894	16/118	EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Other operational conditions affecting workers exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently.
Technical conditions and measures to control dispersion from source towards the worker	No other specific measures identified.

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	24000000 kg/day	---

ESVOC spERC 4.21a.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 6: Uses in coatings**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC7: Industrial spraying</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation</p> <p>PROC15: Use as laboratory reagent</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

**2.1 Contributing scenario controlling environmental exposure for: ERC4**

Amount used	Maximum daily site tonnage (kg/day):	15000 kg/day
	Regional use tonnage (tons/year):	300 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	1
	Annual site tonnage (tons/year):	300 ton(s)/year
Frequency and duration of use	Continuous exposure	20 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	9,8 .10 <sup>-1</sup>
	Emission or Release Factor: Water	7,0 .10 <sup>-5</sup>

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Emission or Release Factor: Soil	0
	initial release prior to RMM	
<p>Technical conditions and measures at process level (source) to prevent release            Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil            Organizational measures to prevent/limit release from the site</p>	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Water	Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): (Degradation effectiveness: 8,4 %)
	Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
	Sediment	Risk from environmental exposure is driven by freshwater sediment.
	Common practices vary across sites thus conservative process release estimates used.	
<p>Conditions and measures related to sewage treatment plant</p>	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m3/d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
<p>Conditions and measures related to external treatment of waste for disposal</p>	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
<p>Conditions and measures related to external recovery of waste</p>	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
<p><b>2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15</b></p>		
<p>Product characteristics</p>	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
<p>Frequency and duration of use</p>	Frequency of use	8 hours/day
<p>Other operational conditions</p>	Assumes use at not more than 20°C above ambient temperature, unless stated	
P5894	19/118	EN

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

affecting workers exposure

differently.

Technical conditions and measures to control dispersion from source towards the worker

General exposures (closed systems)

Handle substance within a closed system.(PROC1)

General exposures (closed systems) with sample collection

Handle substance within a closed system.(PROC2)

Material transfers

Clear transfer lines prior to de-coupling.(PROC8a)

Material transfers

Clear transfer lines prior to de-coupling.(PROC8b)

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	370000 kg/day	---

ESVOC spERC 4.3a.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 7: Uses in coatings**

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC15: Use as laboratory reagent</p> <p>PROC19: Hand-mixing with intimate contact and only PPE available</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p>

**2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d**

Amount used	Maximum daily site tonnage (kg/day):	0,36 kg/day
	Regional use tonnage (tons/year):	260 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,13 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	9,8 .10 <sup>-1</sup>
	Emission or Release Factor: Water	1,0 .10 <sup>-2</sup>
	Emission or Release Factor: Soil	1,0 .10 <sup>-2</sup>
	initial release prior to RMM	

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

<p>Technical conditions and measures at process level (source) to prevent release</p> <p>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</p> <p>Organizational measures to prevent/limit release from the site</p>	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 0 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Soil	Risk from environmental exposure is driven by soil.
	Common practices vary across sites thus conservative process release estimates used.	
<p>Conditions and measures related to sewage treatment plant</p>	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m3/d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
<p>Conditions and measures related to external treatment of waste for disposal</p>	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
<p>Conditions and measures related to external recovery of waste</p>	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
<p><b>2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19</b></p>		
<p>Product characteristics</p>	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
<p>Frequency and duration of use</p>	Frequency of use	8 hours/day
<p>Other operational conditions affecting workers exposure</p>	Outdoor(PROC11)	
	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
<p>Technical conditions and measures to control dispersion from source towards the worker</p>	General exposures (closed systems)	Handle substance within a closed system.(PROC1)
	Filling / preparation of equipment from drums or containers	Handle substance within a closed system.(PROC2)

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

General exposures (closed systems) Use in contained systems	Handle substance within a closed system.(PROC2)
Manual Spraying Indoor.	provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).(PROC11)
Manual Spraying Outdoor.	provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).(PROC11)

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	2400 kg/day	---

ESVOC spERC 8.3b.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.



**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 8: Uses in coatings**

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC1: Adhesives, sealants PC4: Anti-freeze and de-icing products PC8: Biocidal products PC9a: Coatings and paints, thinners, paint removers PC9b: Fillers, putties, plasters, modelling clay PC9c: Finger paints PC15: Non-metal-surface treatment products PC18: Ink and toners PC23: Leather tanning, dye, finishing, impregnation and care products PC24: Lubricants, greases, release products PC31: Polishes and wax blends PC34: Textile dyes, finishing and impregnating products; including bleaches and other processing aids
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

**2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d**

Amount used	Maximum daily site tonnage (kg/day):	0,055 kg/day
	Regional use tonnage (tons/year):	40 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,02 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	9,9 .10 <sup>-1</sup>
	Emission or Release Factor: Water	1,0 .10 <sup>-2</sup>
	Emission or Release Factor: Soil	5,0 .10 <sup>-3</sup>
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and	Water	Risk from environmental exposure is driven by freshwater.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

measures to reduce or limit discharges, air emissions and releases to soil  
Organizational measures to prevent/limit release from the site

Conditions and measures related to sewage treatment plant	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m3/d
	Percentage removed from waste water	96,2 %
Conditions and measures related to external treatment of waste for disposal	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling consumer exposure for: PC1: Glues, hobby use**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	9 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35,73 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.3 Contributing scenario controlling consumer exposure for: PC1: Glues DIY-use (carpet glue, tile glue, wood parquet glue)**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 30%
-------------------------	---	---------------------------------

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	6,39 kg
Frequency and duration of use	Frequency of use	1 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 110 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.4 Contributing scenario controlling consumer exposure for: PC1: Glue from spray**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	85,05 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35,73 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.5 Contributing scenario controlling consumer exposure for: PC1: Sealants**

Product characteristics	Concentration of the Substance in	Covers concentrations up to 30%
-------------------------	-----------------------------------	---------------------------------

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Mixture/Article	
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	75 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	60 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35,73 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
<b>2.6 Contributing scenario controlling consumer exposure for: PC4: Washing car window</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 1%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	0,5 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
<b>2.7 Contributing scenario controlling consumer exposure for: PC4: Pouring into radiator</b>		
Product characteristics	Concentration of the	Covers concentrations up to 10%
P5894	27/118	EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Substance in Mixture/Article	
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	2 kg
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.8 Contributing scenario controlling consumer exposure for: PC4: Lock de-icer**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	4 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	15 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 214,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.9 Contributing scenario controlling consumer exposure for: PC8: Laundry and dish washing**

P5894	28/118	EN
-------	--------	----

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**products**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 5%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	15 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	30 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.10 Contributing scenario controlling consumer exposure for: PC8: Cleaners, liquids**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 5%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	27 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

protection and hygiene)

**2.11 Contributing scenario controlling consumer exposure for: PC8: Cleaners, trigger sprays**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 15%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.12 Contributing scenario controlling consumer exposure for: PC9a: Waterborne latex wall paint, PC15: Waterborne latex wall paint**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 1,5%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	2,76 kg
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	132 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related	Consumer Measures	No specific risk management measure identified

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

to protection of consumer (e.g. behavioural advice, personal protection and hygiene)		beyond those operational conditions stated.
--	--	---

**2.13 Contributing scenario controlling consumer exposure for: PC9a: Solvent rich, high solid, water borne paint, PC15: Solvent rich, high solid, water borne paint**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 27,5%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	744 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	132 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.14 Contributing scenario controlling consumer exposure for: PC9a: Aerosol spray can, PC15: Aerosol spray can**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	215 g
Frequency and duration of use	Frequency of use	2 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational	Room size	34 m3



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

conditions affecting consumers exposure	Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.15 Contributing scenario controlling consumer exposure for: PC9a: Removers (paint-, glue-, wall paper-, sealant-remover), PC15: Removers (paint-, glue-, wall paper-, sealant remover)**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	491 g
Frequency and duration of use	Frequency of use	3 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.16 Contributing scenario controlling consumer exposure for: PC9b: Fillers and putty**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 2%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	85 g
Frequency and duration of use	Frequency of use	12 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by	Exposed skin areas	Covers skin contact area up to 35,73 cm <sup>2</sup>

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

risk management

Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.17 Contributing scenario controlling consumer exposure for: PC9b: Plasters and floor equalizers**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 2%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	13,8 kg
Frequency and duration of use	Frequency of use	12 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.18 Contributing scenario controlling consumer exposure for: PC9b: Modelling clay**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 1%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event (swallowed)	1 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 254,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.19 Contributing scenario controlling consumer exposure for: PC9c: Finger paints**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	1,35 g
	(swallowed)	
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 254,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.20 Contributing scenario controlling consumer exposure for: PC18**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	40 g

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	132 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 71,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.21 Contributing scenario controlling consumer exposure for: PC23: Polishes, wax/cream (floor, furniture, shoes)**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	56 g
Frequency and duration of use	Frequency of use	29 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	73,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.22 Contributing scenario controlling consumer exposure for: PC23: Polishes, spray (furniture, shoes)**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Amount used	Amount used per event	56 g
Frequency and duration of use	Frequency of use	8 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.23 Contributing scenario controlling consumer exposure for: PC24: Liquids**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 100%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	2,2 kg
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.24 Contributing scenario controlling consumer exposure for: PC24: Pastes**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 20%
	Physical Form (at time of use)	liquid

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Vapour pressure	> 10 Pa
Amount used	Amount used per event	34 g
Frequency and duration of use	Frequency of use	10 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.25 Contributing scenario controlling consumer exposure for: PC24: Sprays**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	73 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.26 Contributing scenario controlling consumer exposure for: PC31: Polishes, wax / cream (floor, furniture, shoes)**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
-------------------------	---	---------------------------------

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	142 g
Frequency and duration of use	Frequency of use	29 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	73,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.27 Contributing scenario controlling consumer exposure for: PC31: Polishes, spray (furniture, shoes)**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	8 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.28 Contributing scenario controlling consumer exposure for: PC34**

Product characteristics	Concentration of the	Covers concentrations up to 10%
-------------------------	----------------------	---------------------------------

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Substance in Mixture/Article	
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	115 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	60 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	640 kg/day	---

ESVOC spERC 8.3c.v1 has been used to evaluate the exposure for the environment.

**Consumers**

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>). Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: <http://www.ecetoc.org/tra> Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES



**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 9: Use in Cleaning Agents**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC7: Industrial spraying PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

**2.1 Contributing scenario controlling environmental exposure for: ERC4**

Amount used	Maximum daily site tonnage (kg/day):	1000 kg/day
	Regional use tonnage (tons/year):	38 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	1
	Annual site tonnage (tons/year):	38 ton(s)/year
Frequency and duration of use	Continuous exposure	20 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	1,0
	Emission or Release Factor: Water	3,0 · 10 <sup>-7</sup>
	Emission or Release Factor: Soil	0
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 70 %)
	Water	No wastewater treatment required.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

measures to reduce or limit discharges, air emissions and releases to soil  
Organizational measures to prevent/limit release from the site

Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
Soil	Risk from environmental exposure is driven by soil.
Common practices vary across sites thus conservative process release estimates used.	

Conditions and measures related to sewage treatment plant

Type of Sewage Treatment Plant	Domestic sewage treatment plant
Flow rate of sewage treatment plant effluent	2.000 m3/d
Degradation efficiency	96,2 %
Percentage removed from waste water	96,2 %
Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
-----------------	---

Conditions and measures related to external recovery of waste

Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
------------------	---

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Other operational conditions affecting workers exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
Technical conditions and measures to control dispersion from source towards the worker	Storage	Store substance within a closed system.(PROC1, PROC2)

**3. Exposure estimation and reference to its source**

**Environment**

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	13000000 kg/day	---

ESVOC spERC 4.4a.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 10: Use in Cleaning Agents**

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC10: Roller application or brushing PROC11: Non industrial spraying PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

**2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d**

Amount used	Maximum daily site tonnage (kg/day):	0,043 kg/day
	Regional use tonnage (tons/year):	31 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,016 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	2,0 .10 <sup>-2</sup>
	Emission or Release Factor: Water	1,0 .10 <sup>-6</sup>
	Emission or Release Factor: Soil	0
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 0 %)
	Water	No wastewater treatment required.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

measures to reduce or limit discharges, air emissions and releases to soil  
Organizational measures to prevent/limit release from the site

Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
Water	Risk from environmental exposure is driven by freshwater.
Common practices vary across sites thus conservative process release estimates used.	

Conditions and measures related to sewage treatment plant

Type of Sewage Treatment Plant	Domestic sewage treatment plant
Flow rate of sewage treatment plant effluent	2.000 m3/d
Degradation efficiency	96,2 %
Percentage removed from waste water	96,2 %
Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
-----------------	---

Conditions and measures related to external recovery of waste

Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
------------------	---

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa

Frequency and duration of use	Frequency of use	8 hours/day
-------------------------------	------------------	-------------

Other operational conditions affecting workers exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
---	---	--

Technical conditions and measures to control dispersion from source towards the worker	Cleaning with high pressure washers Spraying Indoor.	provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Limit the substance content in the mixture to 25 %.(PROC11)
	Cleaning with high pressure washers	Ensure operation is undertaken outdoors. or

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Spraying Outdoor.	Limit the substance content in the mixture to 25 %.(PROC11)
Storage	Store substance within a closed system.(PROC1, PROC2)

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	650 kg/day	---

ESVOC spERC 8.4b.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 11: Use in Cleaning Agents**

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC3: Air care products PC4: Anti-freeze and de-icing products PC8: Biocidal products PC9a: Coatings and paints, thinners, paint removers PC9b: Fillers, putties, plasters, modelling clay PC9c: Finger paints PC24: Lubricants, greases, release products PC35: Washing and cleaning products (including solvent based products) PC38: Welding and soldering products (with flux coatings or flux cores), flux products
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

**2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d**

Amount used	Maximum daily site tonnage (kg/day):	0,01 kg/day
	Regional use tonnage (tons/year):	7,6 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,0038 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	9,5 .10 <sup>-1</sup>
	Emission or Release Factor: Water	2,5 .10 <sup>-2</sup>
	Emission or Release Factor: Soil	2,5 .10 <sup>-2</sup>
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	Water	Risk from environmental exposure is driven by freshwater.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Organizational measures to prevent/limit release from the site

Conditions and measures related to sewage treatment plant	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
	Percentage removed from waste water	96,2 %
Conditions and measures related to external treatment of waste for disposal	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling consumer exposure for: PC3: Aircare, instant action (aerosol sprays)**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	0,1 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	4 Times per day
	Exposure duration per event	15 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.3 Contributing scenario controlling consumer exposure for: PC3: Aircare, continuous action (solid & liquid)**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 10%
	Physical Form (at time of use)	liquid



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Vapour pressure	> 10 Pa
Amount used	Amount used per event	0,48 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	480 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35,7 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.4 Contributing scenario controlling consumer exposure for: PC4: Washing car window**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 1%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	0,5 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.5 Contributing scenario controlling consumer exposure for: PC4: Pouring into radiator**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 10%
	Physical Form (at time of use)	liquid

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	use)	
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	2 kg
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
<b>2.6 Contributing scenario controlling consumer exposure for: PC4: Lock de-icer</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	4 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	15 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 214,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
<b>2.7 Contributing scenario controlling consumer exposure for: PC8: Laundry and dish washing products</b>		
Product characteristics	Concentration of the Substance in	Covers concentrations up to 5%
P5894	49/118	EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Mixture/Article	
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	15 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	30 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
<b>2.8 Contributing scenario controlling consumer exposure for: PC8: Cleaners, liquids</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 5%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	27 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
<b>2.9 Contributing scenario controlling consumer exposure for: PC8: Cleaners, trigger sprays</b>		
Product characteristics	Concentration of the	Covers concentrations up to 15%
P5894	50/118	EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Substance in Mixture/Article	
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.10 Contributing scenario controlling consumer exposure for: PC9a: Waterborne latex wall paint**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 1,5%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	2,76 kg
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	132 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**2.11 Contributing scenario controlling consumer exposure for: PC9a: Solvent rich, high solid, water borne paint**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 27,5%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	744 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	132 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.12 Contributing scenario controlling consumer exposure for: PC9a: Aerosol spray can**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	215 g
Frequency and duration of use	Frequency of use	2 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g.	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

behavioural advice, personal protection and hygiene)

**2.13 Contributing scenario controlling consumer exposure for: PC9a: Removers (paint-, glue-, wall paper-, sealant-remover)**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	491 g
Frequency and duration of use	Frequency of use	3 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.14 Contributing scenario controlling consumer exposure for: PC9b: Fillers and putty**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 2%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	85 g
Frequency and duration of use	Frequency of use	12 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35,73 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
--	-------------------	--

**2.15 Contributing scenario controlling consumer exposure for: PC9b: Plasters and floor equalizers**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 2%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	13,8 kg
Frequency and duration of use	Frequency of use	12 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.16 Contributing scenario controlling consumer exposure for: PC9b: Modelling clay**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 1%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event (swallowed)	1 g
	Amount used per event	13,8 kg
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	480 min

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 254,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.17 Contributing scenario controlling consumer exposure for: PC9c**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event (swallowed)	1,35 g
	Amount used per event	13,8 kg
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	480 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 254,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.18 Contributing scenario controlling consumer exposure for: PC24: Liquids**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 100%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	2,2 kg
Frequency and duration of use	Frequency of use	4 days/year



**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Frequency of use	1 Times per day
	Exposure duration per event	10,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.19 Contributing scenario controlling consumer exposure for: PC24: Pastes**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	34 g
Frequency and duration of use	Frequency of use	10 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.20 Contributing scenario controlling consumer exposure for: PC24: Sprays**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	73 g

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.21 Contributing scenario controlling consumer exposure for: PC35: Laundry and dish washing products**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 5%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	15 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	30 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.22 Contributing scenario controlling consumer exposure for: PC35: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners )**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 5%
	Physical Form (at time of use)	liquid

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Vapour pressure	> 10 Pa
Amount used	Amount used per event	27 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.23 Contributing scenario controlling consumer exposure for: PC35: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 15%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.24 Contributing scenario controlling consumer exposure for: PC38**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 20%
-------------------------	---	---------------------------------

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	12 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	60 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
		Covers use under typical household ventilation.
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	140 kg/day	---

ESVOC spERC 8.4c.v1 has been used to evaluate the exposure for the environment.

**Consumers**

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

within the boundaries set by the ES

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 12: Use as binders and release agents**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC6: Calendering operations</p> <p>PROC7: Industrial spraying</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

**2.1 Contributing scenario controlling environmental exposure for: ERC4**

Amount used	Maximum daily site tonnage (kg/day):	1700 kg/day
	Regional use tonnage (tons/year):	35 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	1
	Annual site tonnage (tons/year):	35 ton(s)/year
Frequency and duration of use	Continuous exposure	20 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	1,0
	Emission or Release Factor: Water	3,0 .10 <sup>-7</sup>
	Emission or Release Factor: Soil	0
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 80 %)

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil  
Organizational measures to prevent/limit release from the site

Water	No wastewater treatment required.
Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
Soil	Risk from environmental exposure is driven by soil.
Common practices vary across sites thus conservative process release estimates used.	

Conditions and measures related to sewage treatment plant

Type of Sewage Treatment Plant	Domestic sewage treatment plant
Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
Degradation efficiency	96,2 %
Percentage removed from waste water	96,2 %
Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
-----------------	---

Conditions and measures related to external recovery of waste

Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
------------------	---

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC6, PROC7, PROC8b, PROC10, PROC13, PROC14**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Other operational conditions affecting workers exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
Technical conditions and measures to control dispersion from source towards the worker	Storage	Store substance within a closed system.(PROC1, PROC2)

**3. Exposure estimation and reference to its source**

**Environment**

P5894

62/118

EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	19000000 kg/day	---

ESVOC spERC 4.10a.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 13: Use as binders and release agents**

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC6: Calendering operations</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p>

**2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d**

Amount used	Maximum daily site tonnage (kg/day):	0,00082 kg/day
	Regional use tonnage (tons/year):	0,6 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,0003 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	9,5 .10 <sup>-1</sup>
	Emission or Release Factor: Water	2,5 .10 <sup>-2</sup>
	Emission or Release Factor: Soil	2,5 .10 <sup>-2</sup>
	initial release prior to RMM	
Technical conditions and measures at process level	Air	Treat air emission to provide a typical removal

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

(source) to prevent release  
 Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil  
 Organizational measures to prevent/limit release from the site

	efficiency of (%): (Efficiency: 0 %)
Water	No wastewater treatment required.
Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
Water	Risk from environmental exposure is driven by freshwater.
Common practices vary across sites thus conservative process release estimates used.	

Conditions and measures related to sewage treatment plant

Type of Sewage Treatment Plant	Domestic sewage treatment plant
Flow rate of sewage treatment plant effluent	2.000 m3/d
Degradation efficiency	96,2 %
Percentage removed from waste water	96,2 %
Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
-----------------	---

Conditions and measures related to external recovery of waste

Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
------------------	---

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC6, PROC8a, PROC8b, PROC10, PROC11, PROC14**

Product characteristics

Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	liquid
Vapour pressure	0,5 - 10 kPa

Frequency and duration of use

Frequency of use	8 hours/day
------------------	-------------

Other operational conditions affecting workers exposure

Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
---	--

Technical conditions and measures to control dispersion from source towards the worker

Bulk transfers (closed systems)	Transfer via enclosed lines.(PROC1)
Bulk transfers (closed systems)	Transfer via enclosed lines.(PROC2)
Bulk transfers (closed systems)	Transfer via enclosed lines.(PROC3)

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Casting operations (open systems) Elevated temperature	provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Avoid carrying out operation for more than 4 hours.(PROC6)
Spraying Machine	provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Avoid carrying out operation for more than 4 hours.(PROC11)
Spraying Manual	provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Avoid carrying out operation for more than 4 hours.(PROC11)
Storage	Store substance within a closed system.(PROC1, PROC2)

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	12 kg/day	---

ESVOC spERC 8.10b.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Assumes a good basic standard of occupational hygiene is implemented.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 14: Use as a fuel**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC16: Using material as fuel sources, limited exposure to unburned product to be expected
Environmental Release Categories	ERC7: Industrial use of substances in closed systems

**2.1 Contributing scenario controlling environmental exposure for: ERC7**

Amount used	Maximum daily site tonnage (kg/day):	500 kg/day
	Regional use tonnage (tons/year):	10 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	1
	Annual site tonnage (tons/year):	10 ton(s)/year
Frequency and duration of use	Continuous exposure	20 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	5,0 .10 <sup>-2</sup>
	Emission or Release Factor: Water	1,0 .10 <sup>-5</sup>
	Emission or Release Factor: Soil	0
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 95 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Organizational measures to prevent/limit release from the site

Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
Sediment	Risk from environmental exposure is driven by freshwater sediment.
Common practices vary across sites thus conservative process release estimates used.	

Conditions and measures related to sewage treatment plant

Type of Sewage Treatment Plant	Domestic sewage treatment plant
Flow rate of sewage treatment plant effluent	2.000 m3/d
Degradation efficiency	96,2 %
Percentage removed from waste water	96,2 %
Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	Combustion emissions limited by required exhaust emission controls., Combustion emissions considered in regional exposure assessment.
-----------------	---

Conditions and measures related to external recovery of waste

Recovery Methods	This substance is consumed during use and no waste of the substance is generated.
------------------	---

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16**

Product characteristics

Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	liquid
Vapour pressure	0,5 - 10 kPa

Frequency and duration of use

Frequency of use	8 hours/day
------------------	-------------

Other operational conditions affecting workers exposure

Assumes use at not more than 20°C above ambient temperature, unless stated differently.
---

Technical conditions and measures to control dispersion from source towards the worker

General exposures (closed systems)	Handle substance within a closed system.(PROC1)
General exposures (closed systems)	Handle substance within a closed system.(PROC2)
General exposures (closed systems)	Handle substance within a closed system.(PROC3)
Bulk transfers	Handle substance within a closed system.(PROC8b)
Use as a fuel (closed systems)	Handle substance within a closed system.(PROC16)

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Storage	Store substance within a closed system.(PROC1, PROC2)
---------	---

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	2600000 kg/day	---

ESVOC spERC 7.12a.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 15: Use as a fuel**

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC16: Using material as fuel sources, limited exposure to unburned product to be expected
Environmental Release Categories	ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

**2.1 Contributing scenario controlling environmental exposure for: ERC9a, ERC9b**

Amount used	Maximum daily site tonnage (kg/day):	0,014 kg/day
	Regional use tonnage (tons/year):	10 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,005 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	1,0 .10 <sup>-3</sup>
	Emission or Release Factor: Water	1,0 .10 <sup>-5</sup>
	Emission or Release Factor: Soil	1,0 .10 <sup>-5</sup>
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 0 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.



**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Organizational measures to prevent/limit release from the site

Water	Risk from environmental exposure is driven by freshwater.
Common practices vary across sites thus conservative process release estimates used.	

Conditions and measures related to sewage treatment plant

Type of Sewage Treatment Plant	Domestic sewage treatment plant
Flow rate of sewage treatment plant effluent	2.000 m3/d
Degradation efficiency	96,2 %
Percentage removed from waste water	96,2 %
Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	Combustion emissions limited by required exhaust emission controls., Combustion emissions considered in regional exposure assessment.
-----------------	---

Conditions and measures related to external recovery of waste

Recovery Methods	This substance is consumed during use and no waste of the substance is generated.
------------------	---

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16**

Product characteristics

Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	liquid
Vapour pressure	0,5 - 10 kPa

Frequency and duration of use

Frequency of use	8 hours/day
------------------	-------------

Other operational conditions affecting workers exposure

Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures to control dispersion from source towards the worker

General exposures (closed systems)	Handle substance within a closed system.(PROC1)
General exposures (closed systems)	Handle substance within a closed system.(PROC2)
General exposures (closed systems)	Handle substance within a closed system.(PROC3)
Bulk transfers	Handle substance within a closed system. Clear transfer lines prior to de-coupling.(PROC8b)
Use as a fuel (closed systems)	Handle substance within a closed system.(PROC16)
Storage	Store substance within a closed system.(PROC1, PROC2)

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	210 kg/day	---

ESVOC spERC 9.12b.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 16: Use as a fuel**

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC13: Fuels
Environmental Release Categories	ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

**2.1 Contributing scenario controlling environmental exposure for: ERC9a, ERC9b**

Amount used	Maximum daily site tonnage (kg/day):	0,014 kg/day
	Regional use tonnage (tons/year):	10 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,005 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	1,0 .10 <sup>-3</sup>
	Emission or Release Factor: Water	1,0 .10 <sup>-5</sup>
	Emission or Release Factor: Soil	1,0 .10 <sup>-5</sup>
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Water	Risk from environmental exposure is driven by freshwater.
Conditions and measures related to sewage treatment plant	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
	Percentage removed from waste water	96,2 %

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Conditions and measures related to external treatment of waste for disposal	Waste treatment	Combustion emissions limited by required exhaust emission controls., Combustion emissions considered in regional exposure assessment.
Conditions and measures related to external recovery of waste	Recovery Methods	This substance is consumed during use and no waste of the substance is generated.

**2.2 Contributing scenario controlling consumer exposure for: PC13: Liquid: Automotive Refuelling**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 100%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	37,5 kg
Frequency and duration of use	Frequency of use	52 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	3 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 210 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	100 m <sup>3</sup>
	Covers outdoor use.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.3 Contributing scenario controlling consumer exposure for: PC13: Liquid: Scooter Refuelling**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 100%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	3,75 kg
Frequency and duration of use	Frequency of use	52 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 210 cm <sup>2</sup>

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Other given operational conditions affecting consumers exposure

Room size 100 m<sup>3</sup>

Covers outdoor use.

Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)

Consumer Measures

No specific risk management measure identified beyond those operational conditions stated.

**2.4 Contributing scenario controlling consumer exposure for: PC13: Liquid: Garden Equipment - Use**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 100%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	750 g
Frequency and duration of use	Frequency of use	26 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Other given operational conditions affecting consumers exposure	Room size	100 m <sup>3</sup>
	Covers outdoor use.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.5 Contributing scenario controlling consumer exposure for: PC13: Liquid: Garden Equipment - Refueling**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 100%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	750 g
Frequency and duration of use	Frequency of use	26 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1,8 min
Human factors not influenced by	Exposed skin areas	Covers skin contact area up to 420 cm <sup>2</sup>

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

risk management

Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.6 Contributing scenario controlling consumer exposure for: PC13: Liquid: home space heater fuel**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 100%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	3 kg
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 210 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.7 Contributing scenario controlling consumer exposure for: PC13: Liquid: Lamp oil**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 100%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	100 g
Frequency and duration of use	Frequency of use	52 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	0,6 min

P5894

77/118

EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	event	
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 210 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	210 kg/day	---

ESVOC spERC 9.12c.v1 has been used to evaluate the exposure for the environment.

**Consumers**

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 17: Use as lubricants**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure          PROC2: Use in closed, continuous process with occasional controlled exposure          PROC3: Use in closed batch process (synthesis or formulation)          PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises          PROC7: Industrial spraying          PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities          PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities          PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)          PROC10: Roller application or brushing          PROC13: Treatment of articles by dipping and pouring          PROC17: Lubrication at high energy conditions and in partly open process          PROC18: Greasing at high energy conditions</p>
Environmental Release Categories	<p>ERC4: Industrial use of processing aids in processes and products, not becoming part of articles          ERC7: Industrial use of substances in closed systems</p>

**2.1 Contributing scenario controlling environmental exposure for: ERC4, ERC7**

Amount used	Maximum daily site tonnage (kg/day):	1200 kg/day
	Regional use tonnage (tons/year):	24 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	1
	Annual site tonnage (tons/year):	24 ton(s)/year
Frequency and duration of use	Continuous exposure	20 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	1,0 .10 <sup>-2</sup>
	Emission or Release Factor: Water	3,0 .10 <sup>-6</sup>
	Emission or Release Factor: Soil	1,0 .10 <sup>-3</sup>



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

initial release prior to RMM		
<p>Technical conditions and measures at process level (source) to prevent release            Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil            Organizational measures to prevent/limit release from the site</p>	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 70 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
	Sediment	Risk from environmental exposure is driven by freshwater sediment.
	Common practices vary across sites thus conservative process release estimates used.	
<p>Conditions and measures related to sewage treatment plant</p>	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
<p>Conditions and measures related to external treatment of waste for disposal</p>	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
<p>Conditions and measures related to external recovery of waste</p>	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
<p><b>2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17, PROC18</b></p>		
<p>Product characteristics</p>	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
<p>Frequency and duration of use</p>	Frequency of use	8 hours/day
<p>Other operational conditions affecting workers exposure</p>	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
<p>Technical conditions and measures to control dispersion from source towards the worker</p>	Storage	Store substance within a closed system.(PROC1, PROC2)
<p>P5894 <span style="margin-left: 200px;">80/118</span> <span style="float: right;">EN</span></p>		

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	8500000 kg/day	---

ESVOC spERC 4.6a.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 18: Use as lubricants**

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure          PROC2: Use in closed, continuous process with occasional controlled exposure          PROC3: Use in closed batch process (synthesis or formulation)          PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises          PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities          PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities          PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)          PROC10: Roller application or brushing          PROC11: Non industrial spraying          PROC13: Treatment of articles by dipping and pouring          PROC17: Lubrication at high energy conditions and in partly open process          PROC18: Greasing at high energy conditions          PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems          ERC8d: Wide dispersive outdoor use of processing aids in open systems          ERC9a: Wide dispersive indoor use of substances in closed systems          ERC9b: Wide dispersive outdoor use of substances in closed systems</p>

**2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d, ERC9a, ERC9b**

Amount used	Maximum daily site tonnage (kg/day):	0,016 kg/day
	Regional use tonnage (tons/year):	12 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,0059 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	4,0 .10 <sup>-1</sup> (ERC8a, ERC8d)

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Emission or Release Factor: Water	5,0 .10 <sup>-2</sup> (ERC8a, ERC8d)
	Emission or Release Factor: Soil	5,0 .10 <sup>-2</sup> (ERC8a, ERC8d)
	initial release prior to RMM (ERC8a, ERC8d)	
	Emission or Release Factor: Air	1,0 .10 <sup>-2</sup> (ERC9a, ERC9b)
	Emission or Release Factor: Water	1,0 .10 <sup>-2</sup> (ERC9a, ERC9b)
	Emission or Release Factor: Soil	1,0 .10 <sup>-2</sup> (ERC9a, ERC9b)
	initial release prior to RMM (ERC9a, ERC9b)	
<p>Technical conditions and measures at process level (source) to prevent release</p> <p>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</p> <p>Organizational measures to prevent/limit release from the site</p>	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 0 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Water	Risk from environmental exposure is driven by freshwater.
	Common practices vary across sites thus conservative process release estimates used.	
<p>Conditions and measures related to sewage treatment plant</p>	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
<p>Conditions and measures related to external treatment of waste for disposal</p>	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
<p>Conditions and measures related to external recovery of waste</p>	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
<p><b>2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17, PROC18, PROC20</b></p>		
Product characteristics	Concentration of the Substance in	Covers percentage substance in the product up to 100 % (unless stated differently).
P5894	83/118	EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Mixture/Article	
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Other operational conditions affecting workers exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1)
	General exposures (closed systems)	Handle substance within a closed system.(PROC2)
	General exposures (closed systems)	Handle substance within a closed system.(PROC3)
	Maintenance of small items Elevated temperature Non-dedicated facility	Drain down system prior to equipment break-in or maintenance.(PROC8a)
	Spraying	provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).(PROC11)
	Storage	Store substance within a closed system.(PROC1, PROC2)

**3. Exposure estimation and reference to its source**

**Environment**

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC8a, ERC8d	---	---	Msafe	170 kg/day	---
ERC9a, ERC9b	---	---	Msafe	220 kg/day	---

ESVOC spERC 8.6c.v1 has been used to evaluate the exposure for the environment. ESVOC spERC 9.6b.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 19: Use as lubricants**

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC1: Adhesives, sealants PC24: Lubricants, greases, release products PC31: Polishes and wax blends
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

**2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d, ERC9a, ERC9b**

Amount used	Maximum daily site tonnage (kg/day):	0,0068 kg/day
	Regional use tonnage (tons/year):	5 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,0025 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	4,0 .10 <sup>-1</sup> (ERC8a, ERC8d)
	Emission or Release Factor: Water	5,0 .10 <sup>-2</sup> (ERC8a, ERC8d)
	Emission or Release Factor: Soil	5,0 .10 <sup>-2</sup> (ERC8a, ERC8d)
	initial release prior to RMM (ERC8a, ERC8d)	
	Emission or Release Factor: Air	1,0 .10 <sup>-2</sup> (ERC9a, ERC9b)
	Emission or Release Factor: Water	1,0 .10 <sup>-2</sup> (ERC9a, ERC9b)
	Emission or Release Factor: Soil	1,0 .10 <sup>-2</sup> (ERC9a, ERC9b)
	initial release prior to RMM (ERC9a, ERC9b)	
Technical conditions and measures at process level (source) to prevent release	Water	Risk from environmental exposure is driven by freshwater.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil  
Organizational measures to prevent/limit release from the site

Conditions and measures related to sewage treatment plant	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m3/d
	Percentage removed from waste water	96,2 %
Conditions and measures related to external treatment of waste for disposal	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling consumer exposure for: PC1: Glues, hobby use**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	9 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35,73 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.3 Contributing scenario controlling consumer exposure for: PC1: Glues DIY-use (carpet glue, tile glue, wood parquet glue)**

Product characteristics	Concentration of the Substance in	Covers concentrations up to 30%
-------------------------	-----------------------------------	---------------------------------



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Mixture/Article	
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	6,39 kg
Frequency and duration of use	Frequency of use	1 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 110 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
<b>2.4 Contributing scenario controlling consumer exposure for: PC1: Glue from spray</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	85,05 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35,73 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
<b>2.5 Contributing scenario controlling consumer exposure for: PC1: Sealants</b>		
Product characteristics	Concentration of the	Covers concentrations up to 30%
P5894	88/118	EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Substance in Mixture/Article	
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	75 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	60 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35,73 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.6 Contributing scenario controlling consumer exposure for: PC24: Liquids**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 100%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	2,2 kg
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.7 Contributing scenario controlling consumer exposure for: PC24: Pastes**

P5894	89/118	EN
-------	--------	----

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	34 g
Frequency and duration of use	Frequency of use	10 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.8 Contributing scenario controlling consumer exposure for: PC24: Sprays**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	73 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**2.9 Contributing scenario controlling consumer exposure for: PC31: Polishes, wax / cream (floor, furniture, shoes)**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	142 g
Frequency and duration of use	Frequency of use	29 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	73,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**2.10 Contributing scenario controlling consumer exposure for: PC31: Polishes, spray (furniture, shoes)**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	8 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19,8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation.	
Conditions and measures related	Consumer Measures	No specific risk management measure identified

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

to protection of consumer (e.g. behavioural advice, personal protection and hygiene)

beyond those operational conditions stated.

**3. Exposure estimation and reference to its source**

**Environment**

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC8a, ERC8d	---	---	Msafe	100 kg/day	---
ERC9a, ERC9b	---	---	Msafe	88 kg/day	---

ESVOC spERC 8.6e.v1 has been used to evaluate the exposure for the environment. ESVOC spERC 9.6d.v1 has been used to evaluate the exposure for the environment.

**Consumers**

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 20: Use as Functional Fluids**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure            PROC2: Use in closed, continuous process with occasional controlled exposure            PROC3: Use in closed batch process (synthesis or formulation)            PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises            PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities            PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities            PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p>
Environmental Release Categories	ERC7: Industrial use of substances in closed systems

**2.1 Contributing scenario controlling environmental exposure for: ERC7**

Amount used	Maximum daily site tonnage (kg/day):	250 kg/day
	Regional use tonnage (tons/year):	5 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	1
	Annual site tonnage (tons/year):	5 ton(s)/year
Frequency and duration of use	Continuous exposure	20 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	1,0 .10 <sup>-2</sup>
	Emission or Release Factor: Water	3,0 .10 <sup>-6</sup>
	Emission or Release Factor: Soil	1,0 .10 <sup>-3</sup>
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 0 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant,

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

discharges, air emissions and releases to soil  
Organizational measures to prevent/limit release from the site

	no onsite wastewater treatment required.
Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
Water	Risk from environmental exposure is driven by freshwater.
Common practices vary across sites thus conservative process release estimates used.	

Conditions and measures related to sewage treatment plant

Type of Sewage Treatment Plant	Domestic sewage treatment plant
Flow rate of sewage treatment plant effluent	2.000 m3/d
Degradation efficiency	96,2 %
Percentage removed from waste water	96,2 %
Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
-----------------	---

Conditions and measures related to external recovery of waste

Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
------------------	---

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Other operational conditions affecting workers exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
Technical conditions and measures to control dispersion from source towards the worker	Storage	Store substance within a closed system.(PROC1, PROC2)

**3. Exposure estimation and reference to its source**

**Environment**

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	2700000 kg/day	---

ESVOC spERC 7.13a.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  
 Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 21: Use as Functional Fluids**

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems
Environmental Release Categories	ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

**2.1 Contributing scenario controlling environmental exposure for: ERC9a, ERC9b**

Amount used	Maximum daily site tonnage (kg/day):	0,0055 kg/day
	Regional use tonnage (tons/year):	4 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,002 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	5,0 .10 <sup>-2</sup>
	Emission or Release Factor: Water	2,5 .10 <sup>-2</sup>
	Emission or Release Factor: Soil	2,5 .10 <sup>-2</sup>
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 0 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Organizational measures to prevent/limit release from the site

Water	Risk from environmental exposure is driven by freshwater.
Common practices vary across sites thus conservative process release estimates used.	

Conditions and measures related to sewage treatment plant

Type of Sewage Treatment Plant	Domestic sewage treatment plant
Flow rate of sewage treatment plant effluent	2.000 m3/d
Degradation efficiency	96,2 %
Percentage removed from waste water	96,2 %
Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
-----------------	---

Conditions and measures related to external recovery of waste

Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
------------------	---

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC9, PROC20**

Product characteristics

Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	liquid
Vapour pressure	0,5 - 10 kPa

Frequency and duration of use

Frequency of use	8 hours/day
------------------	-------------

Other operational conditions affecting workers exposure

Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures to control dispersion from source towards the worker

Storage	Store substance within a closed system.(PROC1, PROC2)
---------	---

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	77 kg/day	---

ESVOC spERC 9.13b.v1 has been used to evaluate the exposure for the environment.

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 22: Use as Functional Fluids**

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC16: Heat transfer fluids PC17: Hydraulic fluids
Environmental Release Categories	ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

**2.1 Contributing scenario controlling environmental exposure for: ERC9a, ERC9b**

Amount used	Maximum daily site tonnage (kg/day):	0,0027 kg/day
	Regional use tonnage (tons/year):	2 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,001 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	5,0 .10 <sup>-2</sup>
	Emission or Release Factor: Water	2,5 .10 <sup>-2</sup>
	Emission or Release Factor: Soil	2,5 .10 <sup>-2</sup>
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Water	Risk from environmental exposure is driven by freshwater.
Conditions and measures related to sewage treatment plant	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
	Percentage removed	96,2 %

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	from waste water	
Conditions and measures related to external treatment of waste for disposal	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling consumer exposure for: PC16, PC17**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 100%
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 Pa
Amount used	Amount used per event	2,2 kg
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10,2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	40 kg/day	---

ESVOC spERC 9.13c.v1 has been used to evaluate the exposure for the environment.

**Consumers**

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

P5894 100/118 EN

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 23: Use in laboratories**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC10: Roller application or brushing PROC15: Use as laboratory reagent
Environmental Release Categories	ERC2: Formulation of preparations ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

**2.1 Contributing scenario controlling environmental exposure for: ERC2, ERC4**

Amount used	Maximum daily site tonnage (kg/day):	30 kg/day
	Regional use tonnage (tons/year):	0,6 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	1
	Annual site tonnage (tons/year):	0,6 ton(s)/year
Frequency and duration of use	Continuous exposure	20 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	2,5 .10 <sup>-2</sup>
	Emission or Release Factor: Water	2,0 .10 <sup>-2</sup>
	Emission or Release Factor: Soil	1,0 .10 <sup>-4</sup>
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 0 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
	Sediment	Risk from environmental exposure is driven by freshwater sediment.
	Common practices vary across sites thus conservative process release estimates used.	

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Conditions and measures related to sewage treatment plant	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
Conditions and measures related to external treatment of waste for disposal	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling worker exposure for: PROC10, PROC15**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Other operational conditions affecting workers exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	1300 kg/day	---

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may



*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

be necessary to define appropriate site-specific risk management measures.  
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 24: Use in laboratories**

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC10: Roller application or brushing PROC15: Use as laboratory reagent
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems

**2.1 Contributing scenario controlling environmental exposure for: ERC8a**

Amount used	Maximum daily site tonnage (kg/day):	0,0011 kg/day
	Regional use tonnage (tons/year):	0,8 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,0004 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	5,0 .10 <sup>-1</sup>
	Emission or Release Factor: Water	5,0 .10 <sup>-1</sup>
	Emission or Release Factor: Soil	0
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 0 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Water	Risk from environmental exposure is driven by freshwater.
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to sewage treatment plant	Type of Sewage Treatment Plant	Domestic sewage treatment plant

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Flow rate of sewage treatment plant effluent	2.000 m3/d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
Conditions and measures related to external treatment of waste for disposal	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling worker exposure for: PROC10, PROC15**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Other operational conditions affecting workers exposure	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	13 kg/day	---

ESVOC spERC 8.17.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 25: Use in metal working fluids / rolling oils**

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC7: Industrial spraying</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC17: Lubrication at high energy conditions and in partly open process</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

**2.1 Contributing scenario controlling environmental exposure for: ERC4**

Amount used	Maximum daily site tonnage (kg/day):	740 kg/day
	Regional use tonnage (tons/year):	15 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	1
	Annual site tonnage (tons/year):	15 ton(s)/year
Frequency and duration of use	Continuous exposure	20 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	2,0 .10 <sup>-2</sup>
	Emission or Release Factor: Water	3,0 .10 <sup>-6</sup>
	Emission or Release Factor: Soil	0

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

initial release prior to RMM		
<p>Technical conditions and measures at process level (source) to prevent release            Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil            Organizational measures to prevent/limit release from the site</p>	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 70 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Water	Prevent discharge of undissolved substance to or recover from onsite wastewater.
	Sediment	Risk from environmental exposure is driven by freshwater sediment.
	Common practices vary across sites thus conservative process release estimates used.	
<p>Conditions and measures related to sewage treatment plant</p>	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
<p>Conditions and measures related to external treatment of waste for disposal</p>	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
<p>Conditions and measures related to external recovery of waste</p>	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
<p><b>2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17</b></p>		
<p>Product characteristics</p>	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
<p>Frequency and duration of use</p>	Frequency of use	8 hours/day
<p>Other operational conditions affecting workers exposure</p>	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
<p>Technical conditions and measures to control dispersion from source towards the worker</p>	General exposures (closed systems)	Handle substance within a closed system.(PROC1)

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

General exposures (closed systems)	Handle substance within a closed system.(PROC2)
General exposures (closed systems)	Handle substance within a closed system.(PROC3)
Bulk transfers	Clear transfer lines prior to de-coupling.(PROC8b)
Treatment by dipping and pouring	Allow time for product to drain from workpiece.(PROC13)
Storage	Store substance within a closed system. Transfer via enclosed lines.(PROC1, PROC2)

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	8500000 kg/day	---

ESVOC spERC 4.7a.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 26: Use in metal working fluids / rolling oils**

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC17: Lubrication at high energy conditions and in partly open process</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p>

**2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d**

Amount used	Maximum daily site tonnage (kg/day):	0,01 kg/day
	Regional use tonnage (tons/year):	7,4 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,0037 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	4,0 .10 <sup>-1</sup>
	Emission or Release Factor: Water	5,0 .10 <sup>-2</sup>
	Emission or Release Factor: Soil	5,0 .10 <sup>-2</sup>
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 0 %)



**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil  
Organizational measures to prevent/limit release from the site

Water	No wastewater treatment required.
Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
Water	Risk from environmental exposure is driven by freshwater.
Common practices vary across sites thus conservative process release estimates used.	

Conditions and measures related to sewage treatment plant

Type of Sewage Treatment Plant	Domestic sewage treatment plant
Flow rate of sewage treatment plant effluent	2.000 m3/d
Degradation efficiency	96,2 %
Percentage removed from waste water	96,2 %
Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to external treatment of waste for disposal

Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
-----------------	---

Conditions and measures related to external recovery of waste

Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.
------------------	---

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17**

Product characteristics

Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	liquid
Vapour pressure	0,5 - 10 kPa

Frequency and duration of use

Frequency of use	8 hours/day
------------------	-------------

Other operational conditions affecting workers exposure

Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Technical conditions and measures to control dispersion from source towards the worker

General exposures (closed systems)	Handle substance within a closed system.(PROC1)
General exposures (closed systems)	Handle substance within a closed system.(PROC2)
General exposures (closed systems)	Handle substance within a closed system.(PROC3)
Spraying	provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).(PROC11)

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Storage

Store substance within a closed system.(PROC1, PROC2)

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	120 kg/day	---

ESVOC spERC 8.7c.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  
 Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  
 Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).  
 Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.  
 For further information on the assessment method, see: <http://www.ecetoc.org/tra>  
 Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 27: Use in road and construction applications**

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC10: Roller application or brushing PROC11: Non industrial spraying PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC8d: Wide dispersive outdoor use of processing aids in open systems ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

**2.1 Contributing scenario controlling environmental exposure for: ERC8d, ERC8f**

Amount used	Maximum daily site tonnage (kg/day):	0,01 kg/day
	Regional use tonnage (tons/year):	7,5 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,0038 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	9,5 .10 <sup>-1</sup>
	Emission or Release Factor: Water	4,0 .10 <sup>-2</sup>
	Emission or Release Factor: Soil	1,0 .10 <sup>-2</sup>
	initial release prior to RMM	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 0 %)
	Water	No wastewater treatment required.
	Water	If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.
	Water	Risk from environmental exposure is driven by freshwater.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to sewage treatment plant	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
	Degradation efficiency	96,2 %
	Percentage removed from waste water	96,2 %
	Sludge Treatment	Do not apply industrial sludge to natural soils., Sludge should be incinerated, contained or reclaimed.
Conditions and measures related to external treatment of waste for disposal	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling worker exposure for: PROC8a, PROC8b, PROC10, PROC11, PROC13**

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0,5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Other operational conditions affecting workers exposure	Outdoor(PROC11)	
	Assumes use at not more than 20°C above ambient temperature, unless stated differently.	
Technical conditions and measures to control dispersion from source towards the worker	Spraying/ fogging by machine application	provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).(PROC11)
	Spraying/ fogging by machine application Elevated temperature	Ensure operation is undertaken outdoors.(PROC11)

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
P5894		115/118			EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

---	---	---	Msafe	150 kg/day	---
-----	-----	-----	-------	------------	-----

ESVOC spERC 8.15.v1 has been used to evaluate the exposure for the environment.

**Workers**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

**Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

**SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

**1. Short title of Exposure Scenario 28: Other consumer uses**

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC28: Perfumes, fragrances PC39: Cosmetics, personal care products
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

**2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d**

Amount used	Maximum daily site tonnage (kg/day):	0,00027 kg/day
	Regional use tonnage (tons/year):	0,2 ton(s)/year
	Fraction of EU tonnage used in region:	0,1
	Fraction of Regional tonnage used locally:	0,0005
	Annual site tonnage (tons/year):	0,0001 ton(s)/year
Frequency and duration of use	Continuous exposure	365 days/year
Environment factors not influenced by risk management	Dilution Factor (River)	10
	Dilution Factor (Coastal Areas)	100
Other given operational conditions affecting environmental exposure	Emission or Release Factor: Air	9,5 .10 <sup>-1</sup>
	Emission or Release Factor: Water	2,5 .10 <sup>-2</sup>
	Emission or Release Factor: Soil	2,5 .10 <sup>-2</sup>
	initial release prior to RMM	
Conditions and measures related to sewage treatment plant	Type of Sewage Treatment Plant	Domestic sewage treatment plant
	Flow rate of sewage treatment plant effluent	2.000 m <sup>3</sup> /d
	Percentage removed from waste water	96,2 %
Conditions and measures related to external treatment of waste for disposal	Waste treatment	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	Recovery Methods	External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling consumer exposure for: PC28, PC39**

P5894 117/118 EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Version 1.2

Print Date 06.10.2014

Revision date / valid from 06.10.2014

Consumer uses e.g. as a carrier in cosmetics/personal care products, perfumes and fragrances. Note: For cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation.

**3. Exposure estimation and reference to its source**

**Environment**

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
---	---	---	Msafe	4,2 kg/day	---

ESVOC spERC 8.16.v1 has been used to evaluate the exposure for the environment.

**Consumers**

No exposure assessment presented for human health.

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

<b>COMPANY INFORMATION DISTRIBUTOR</b>		
<b>name</b>	<b>BRENNTAG N.V.</b>	<b>BRENNTAG Nederland B.V.</b>
address	Nijverheidslaan 38 8540 Deerlijk	Donker Duyvisweg 44 3316 BM Dordrecht
country	Belgium	The Netherlands
phone number	+32 (0)56 77 69 44	+31 (0)78 65 44 944
fax number	+32 (0)56 77 57 11	+31 (0)78 65 44 919
website	www.brenntag.be	www.brenntag.nl
e-mail	info@brenntag.be	info@brenntag.nl
activities	Distribution and export of chemicals and raw materials	
VAT number	BE0405317567	NL001375945B01
recall procedure available	Yes	
emergency number (24/365)	+32 (0)56 77 69 44	+31 (0)78 6544 944
<b>QUALITY SYSTEMS</b>		
ISO 9001	Yes	Yes
ISO 14001	Yes	Yes
ISO 22000	Yes	Yes
FSSC 22000	Yes	Yes
GMP+ -feed	Yes	Yes
OHSAS18001	-	Yes
ESAD	Yes	Yes
other	-	AEO